

PAT-NO: JP359227992A

DOCUMENT-IDENTIFIER: JP 59227992 A

TITLE: LUBRICANT FOR PLASTIC WORKING

PUBN-DATE: December 21, 1984

INVENTOR-INFORMATION:

NAME

OKIMOTO, KUNIO

SATO, TOMIO

YAMAKAWA, TOSHIO

ASSIGNEE-INFORMATION:

NAME

COUNTRY

AGENCY OF IND SCIENCE & TECHNOL

N/A

APPL-NO: JP58103352

APPL-DATE: June 8, 1983

INT-CL (IPC): C10M007/28, C10M007/30 , C10M007/48

US-CL-CURRENT: 508/542

ABSTRACT:

PURPOSE: To provide a lubricant for plastic working composed of a specified heat-resistant resin, a lubricant, an adhesion agent to workpiece and tool, and a solvent and exhibiting excellent lubricating properties and heat resistance.

CONSTITUTION: The lubricant is prep'd. by blending (A) heat resistat resin comprising polyimide, (B) Teflon in powder as lubricant, (C) methylphenylsilicone resin as adhesion agent to workpiece and tool and (D) N-methylpyrrolidone soln. as solvent in an A:B:C:D blend ratio of 1:0.25~2.0:1:5 by weight.

EFFECT: The lubricant is suitable for plastic working, such as forging or deep drawing, and powder molding at 250~350°C.

COPYRIGHT: (C)1984,JPO&Japio